



Product Data Sheet

PETRON 2T PREMIUM

DESCRIPTION

PETRON 2T PREMIUM is a premium quality motorcycle oil recommended for Kawasaki, Suzuki and Yamaha motorcycles as well as other two-stroke gasoline engines.

PROPERTIES

- Better engine protection even at its low recommended dosage, assuring longer engine life
- High detergency that keeps pistons, piston rings, cylinder liners, spark plug and exhaust port clean
- Environment-friendly due to cleaner exhaust emissions
- Economical; for every liter of gasoline only 25 ml of oil is required as compared to the traditional practice of using 50 ml of oil for liter of gasoline; this means savings due to a 50% reduction in oil usage
- Recommended to users who prefer adding the oil to gasoline during tank fill-up; may also be poured into the oil reservoir of motorcycles with an autolube system

(Minor adjustments must be made on the autolube calibration to benefit from the savings of using 40:1 fuel to oil ratio)

GRADE

- SAE 30

APPLICATIONS

- Motorcycles, tricycles, small passenger cars, scooters, lawn mowers, small tractors, chainsaws and other portable equipment powered by two-stroke gasoline engines
- Recommended dosages are:

Fuel (in liters)	2T Premium (in ml)
1 liter	25 ml
2 liters	50 ml
3 liters	75 ml
4 liters	100 ml
5 liters	125 ml

QUALITY LEVEL

- It has the performance profile of:
 - API Service TC
 - JASO FB

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.

TYPICAL CHARACTERISTICS

Color, ASTM	L2.5
Specific Gravity at 15°C	0.8853
Kinematic Viscosity at 40°C, cSt	88.02
Kinematic Viscosity at 100°C, cSt	10.57
Viscosity Index	103
Flash Point, COC, °C	248
TBN, mgKOH/g	1.2