



Product Data Sheet

PETRON RIDER 4T PREMIUM MULTI-GRADE SAE 15W-40

DESCRIPTION

PETRON RIDER 4T PREMIUM MULTI-GRADE SAE 15W-40 is a high quality, premium grade motorcycle oil suitable for use for both air-cooled and liquid-cooled four-stroke motorcycles. It is designed to provide improved clutch performance.

It contains TCS or Thermal Control System to enhance the oil's thermal stability, volatility profile and oxidation stability.

PROPERTIES

- Excellent wear protection for longer engine life
- Excellent shear stability to resist oil thinning and breakdown
- Has optimum friction characteristics for good clutch engagement

GRADE

- SAE 15W-40

TYPICAL CHARACTERISTICS

Color, ASTM	1.5
Specific Gravity at 15°C	0.8727
Kinematic Viscosity at 40°C	106.9
Kinematic Viscosity at 100°C	14.40
Viscosity Index	138
Flash Point, COC, °C	228
Pour Point, °C	-27
TBN, mgKOH/g	5.5

APPLICATION

Four-stroke motorcycle engines

QUALITY LEVELS

- It has the performance profile of:
 - API SL
 - JASO MA/MA2

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.