



REV-X MONOGRADE

MALAYSIA

DESCRIPTION

REV-X MONO-GRADE is a high-quality engine oil recommended for use in diesel engines operating under mild to moderate service conditions or short drain intervals. It is suitable for passenger-type vehicles such as jeeps, buses, AUVs, and mixed commercial fleets.

PROPERTIES

- Provides satisfactory performance in engines used under mild operating conditions
- Provides sufficient engine protection against wear and deposits

GRADE

- SAE 10W, 30, 40, 40

APPLICATIONS

- Automotive diesel engines under mild operating conditions requiring short drain intervals

QUALITY LEVEL

- It has the performance profile of:
 - API Service CF/SF

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages

TYPICAL CHARACTERISTICS

	SAE 10W	SAE 30	SAE 40	SAE 50
Specific Gravity at 15.6 °C	0.8979	0.8979	0.8940	0.8979
Flash Point, COC, °C	220	238	230	270
Color, ASTM	L 1.0	1.5	L2.0	L2.0
Viscosity at 40 °C, cSt	29.36	88.58	143.5	194.1
Viscosity at 100 °C, cSt	5.260	10.54	14.55	17.95
Viscosity Index	111	101	100	101
TBN, mg KOH/g	5.8	5.8	5.8	5.8