



## Product Data Sheet

# REV-X MULTIGRADE SAE 20W-50

### DESCRIPTION

**REV-X MULTIGRADE SAE 20W-50** is high-quality engine oil designed for indirect injected diesel engines including off-road vehicles. It can be used for naturally-aspirated, turbo-charged and supercharged diesel engines. It is suitable for mixed fleets of diesel and gasoline-powered vehicles such as trucks and buses.

### PROPERTIES

- Effective control of piston deposits
- High-level protection from wear and copper-based corrosion for longer engine life
- High resistance against oil-thickening and gum-formation

### GRADE

- SAE 20W-50

### APPLICATIONS

- Mixed fleets of automotive diesel and gasoline-powered vehicles such as trucks and buses.
- Can also be used for off-road vehicles, agricultural tractors and equipment

### QUALITY LEVELS

- It has the performance profile of:
  - API CF/SF

### AVAILABLE PACKAGES

Please contact our Sales Team for the available packages

### TYPICAL CHARACTERISTICS

Specific Gravity at 15.6°C	0.8806
Flash Point, COC, °C	224
Kinematic Viscosity at 40°C, cSt	168.7
Kinematic Viscosity at 100°C, cSt	19.11
Viscosity Index	129
TBN, mg KOH/g	6.8

For inquiries, contact  
**Petron Fuel International Sdn Bhd**  
Tel. No. 03-2082 8400

Rev 1: 14 May 2020