



Product Data Sheet

RIDER 4T SYNTHETIC BLEND SAE 10W-40

DESCRIPTION

RIDER 4T SYNTHETIC BLEND SAE 10W-40 is a premium quality, high performance motorcycle engine oil designed to ensure maximum performance even under the most demanding riding conditions. Combined with its synthetic blend base oil and advanced additive technology, it provides excellent friction characteristics for good clutch performance.

It contains TCS or Thermal Control System to enhance the oil's thermal and oxidation stability and volatility profile.

PROPERTIES

- Excellent high temperature air-cooled and water-cooled performance
- Excellent shear stability to resist oil thinning and break down
- Excellent engine protection for longer engine life
- Has excellent friction characteristics for good clutch engagement

GRADE

- SAE 10W-40

APPLICATIONS

- Four-stroke motorcycle engines

QUALITY LEVEL

- It has the performance profile of:
 - API SL
 - JASO MA
 - JASO MA2

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.

TYPICAL CHARACTERISTICS

Specific Gravity at 15°C	0.8612
Flash Point, COC, °C	222
Color, ASTM	1.5
Kinematic Viscosity at 40°C, cSt	89.50
Kinematic Viscosity at 100°C, cSt	14.37
Viscosity Index	167
Pour Point, °C	-39
TBN, mg KOH/g	5.5