



Product Data Sheet

PETRON ATF PREMIUM

DESCRIPTION

PETRON ATF PREMIUM is a mineral grade and multifunctional fluid for automatic and power-shift transmissions. It is designed to meet the tropical country requirements of General Motors Dexron III-H, Ford Mercon, Allison C-4, and Caterpillar TO-2.

PROPERTIES

- Provides quiet operation and smooth shifting
- Resistant to high temperature oxidation and fluid thickening
- Controlled frictional properties and outstanding anti-wear performance
- Provides protection against rusting and corrosion
- Compatibility with commonly used seal materials
- Outstanding hydraulic pump performance

GRADE

- SAE 20

APPLICATIONS

- Automatic transmissions, power steering, hydraulic systems, torque converters in cars, trucks and heavy equipment
- For gearboxes of front-wheel drive cars
- Suitable for use in applications where fluids meet Dexron III-H, Ford Mercon, Allison C-4 or Caterpillar TO-2 performance are recommended

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.

TYPICAL CHARACTERISTICS*

Color, Visual	Red
Density at 15°C, kg/L	0.8515
Kinematic Viscosity at 40°C, cSt	37.31
Kinematic Viscosity at 100°C, cSt	7.775
Viscosity Index	185
Flash Point, COC, °C	210

* Only typical properties and may vary per production batch.