



# PETRON REV-X TURBO HTP

## DESCRIPTION

**PETRON REV-X TURBO HTP** is a high premium, Polyalphaolefin (PAO) – based fully synthetic heavy-duty engine oil recommended for naturally aspirated and turbocharged four-stroke diesel engines. It is specially designed to provide excellent engine protection for newer modern, high-performance vehicles.

## PROPERTIES

- It prevents soot and piston deposits to maintain superior engine cleanliness and efficiency.
- It gives excellent protection against wear and corrosion for longer engine life.
- It has outstanding thermal and oxidation stability to provide extended engine protection.
- It prolongs the life of emissions control systems such as diesel particulate filters (DPF) and exhaust gas recirculation (EGR).

## GRADE

SAE 5W-40

## APPLICATION

- Turbocharged or supercharged high performance heavy duty diesel engines under both low speed-high speed and high speed-high load conditions.
- Light duty trucks
- Gasoline engines requiring an API SN lubricating performance

## QUALITY LEVELS

- It is approved and certified according to specifications of:
  - API CJ-4/SN
  - MAN 3575
  - Cummins CES 20081
  - Volvo VDS-4
  - Mack EO-O Premium Plus
  - Renault VI RLD-3
- It has the performance profile of:
  - ACEA E9

## AVAILABLE PACKAGES

*\*Please contact our Sales Team for the available packages*

## TYPICAL CHARACTERISTICS

Color, ASTM	L2.5
Density at 15.6°C, kg/L	0.8531
Kinematic Viscosity at 40°C, cSt	91.44
Kinematic Viscosity at 100°C, cSt	14.30
Viscosity Index	162
Flash Point, COC, °C	200
TBN, mg KOH/g	10.0