



Product Data Sheet

REV-X PREMIUM MULTI-GRADE 15W-40

DESCRIPTION

REV-X PREMIUM MULTI-GRADE 15W-40 with DC Technology is premium quality engine oil designed to surpass the demanding performance requirements of heavy-duty diesel engines, including off-road vehicles. It is suitable for engines with EGR (exhaust gas recirculation) and other emissions control systems.

The Dynamic Cleaning Technology (DC Tech) sustains engine cleanliness, thus giving a smooth driving experience and longer engine life.

PROPERTIES

- Provide excellent protection against wear and corrosion for longer engine life
- Provide excellent control of soot and piston deposits
- Resist oil-thickening and gum-formation
- Allow for extended oil drain interval

GRADE

- SAE 15W-40

APPLICATIONS

- Turbocharged or supercharged high performance diesel engines operating under both low speed-high load and high speed-high load conditions
- Automotive diesel engines using high sulfur diesel fuels
- Gasoline-powered equipment

QUALITY LEVELS

It has the performance profile of:

- API CJ-4/SN
- ACEA E7-16
- Cummins CES 20081
- Detroit Diesel DFS 93K218
- Mack EO-O Premium
- MAN M 3575
- MB 228.31
- MTU Category 2.1
- Renault VI RLD-3
- Volvo VDS-4

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.

TYPICAL CHARACTERISTICS

Specific Gravity at 15.6 °C	0.8839
Flash Point, COC, °C	240
Color, ASTM	L2.5
Kinematic Viscosity at 40°C, cSt	107.6
Kinematic Viscosity at 100°C, cSt	14.09
Viscosity Index	132
TBN, mg KOH/g	9.8
Pour Point, °C	-33