



BLAZE RACING SYNTHETIC BLEND 5W-30

DESCRIPTION

BLAZE RACING SYNTHETIC BLEND 5W-30 with TS³ is a multi-grade synthetic blend engine oil designed to give maximum engine protection, improved oxidation stability, and better wear protection. It is suitable for passenger cars and light-duty trucks and vans.

The unique additive technology called Thermal Stress Stabilizing System (TS³) keeps the oil stable even at extreme temperatures, providing ultimate protection from engine stress.

PROPERTIES

- Has excellent thermal stability and oxidation resistance for longer oil drain interval
- Provides better volatility and viscosity properties
- Provides excellent wear protection for longer engine life

GRADE

- SAE 5W-30

TYPICAL CHARACTERISTICS

| | |
|-----------------------------------|--------|
| Specific Gravity at 15.6°C | 0.8614 |
| Flash Point, COC, °C | 218 |
| Color, ASTM | 3.0 |
| Kinematic Viscosity at 40°C, cSt | 63.28 |
| Kinematic Viscosity at 100°C, cSt | 10.71 |
| Viscosity Index | 160 |
| TBN, mg KOH/g | 9.5 |

APPLICATION

- Gasoline-powered cars, sports utility vehicles, vans, and light-duty trucks where API SN are recommended

QUALITY LEVEL

- It has the performance profile of:
 - API SN

AVAILABLE PACKAGES

Please contact our Sales Team for the available packages.