

# **PETRON MOLYGREASE EP 2**

## **DESCRIPTION**

**PETRON MOLYGREASE EP 2** is a premium lithium-type grease with extreme pressure characteristics enhanced by the presence of molybdenum disulfide additive.

#### **PROPERTIES**

- Prevents metal-to-metal contact and surface scuffing
- Provides adequate protection in the absence of full-fluid film lubrication
- Reduces wear and protects equipment parts during intermittent, extreme operating and heavy load conditions

## **APPLICATIONS**

- Anti-friction ball and roller bearings
- Automotive wheel bearings and chassis points operating under high load conditions
- Operating temperature up to 120°C

#### **TYPE**

• Lithium-type extreme pressure grease with molybdenum disulfide

#### **AVAILABLE PACKAGES**

Please contact our Sales Team for the available packages.

#### **GRADE**

NLGI No. 2

## **TYPICAL CHARACTERISTICS**

Appearance, Texture	Uniform/Smooth
Color, Visual	Gray
Worked Penetration at 25°C, 100 g, 5 secs. mm/10	
60 strokes	274
10,000 strokes	282
Dropping Point, °C	182
Base oil Viscosity at 40°C, cSt	90.90
Tilted Wheel Bearing Test	
Slump Rating	Pass
Leakage, grams	0.2